

Blasolube 590

Art. 590

Description: Blasolube 590 is an extremely water-resistant high performance grease on a calcium/lithium base, of semi-liquid consistency.

Application: Blasolube 590 is suitable for the lubrication of highly loaded roller and friction bearings under demanding operating conditions which are supplied with lubricant via central lubrication systems. The excellent rheological properties combined with a good low-temperature behavior down to -30 °C allow a broad range of applications. Blasolube 590 is ideally suited for use in central lubrication systems in industry (such as machine tools), on commercial vehicles and on devices with long supply lines that work outdoors.

Product characteristics

- High resistance to water
- Particular high pressure additives
- High work stability
- Optimum wear protection
- Good adherence and good resistance
- High corrosion protection

Advantages

- The lubricity and the sealing properties will remain also under the influence of water
- The lubrication characteristic is guaranteed also under high pressure
- The grease consistency will remain also under strong mechanical stress
- Guarantees a long service life and protection of machine parts
- Long operating life of the lubricant
- Machine parts are protected and remain operable for a long time

Attention! The maximal permissible steady-state temperature is **+100°C**

Physical / chemical data:

	Unit	Parameter	Test method
Application temperature range:	-	-30°C to +100°C	
Grease type:	-	Calcium-/Lithium grease	
Colour, appearance:	-	yellow-green fluorescent	
Alloy type:	-	KP 0 G-30 G 0 G-30	DIN 51502
Penetration class:	-	NLGI 0	DIN 51818
Normal penetration Pw 60 (60 hub at +25°C):	1/10 mm	355-385	ISO 2137
Density at +20°C:	g/cm ³	0.918	DIN 51757
Pour point:	°C	140	ISO 2176
Oil viscosity at 40°C:	mm ² /s	75	DIN 51562-1
Oil separation (after 7 days at 40°C):	%	3	DIN 51817
Shell-Roller Test (mechanical stability):	1/10 mm	390	ASTM D 1831/ISO 2137
EMCOR corrosion protection test:	-	0 / 0	DIN 51802
Speed characteristic (dm x n)	m/min	up to 450	
Flow pressure at -30°C:	mbar	300	DIN 51805

Resistance: See overleaf

Blasolube 590

Art. 590

Resistance:	Resistant against media:	– cold water – warm water – alcalin solutions – acid solutions
--------------------	--------------------------	---

Safety and environmental aspects:	ADR/RID:	Not classified as hazardous by transport regulations.
	Precautions:	Do not allow product to get into ground water, water course or sewage system.
	Water hazard class:	Slightly water endangering (WGK 1)
	EC waste code:	12 01 12
	CH waste code:	Identical to EC waste code (as per VeVA of 01.01.06)
	Classification and labelling:	stated in the safety data sheet



Conditionnements: Drum: 180/50 kg • Canister: 14 kg

The data given on this sheet are based on properties and application possibilities as known to us. Blaser Swisslube AG will assume no liability for damage resulting from the improper use of its products. No general liability can be derived from these data. 31.549 E (0317)