

We have the solution...

...the future has a name



Technical Information

LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: www.lubcon.com

TURMOSYNTHGREASE ALN 4601

LUBCON-Special Grease

TURMOSYNTHGREASE ALN 4601 is a special grease for high specific loads with a temperature range from -30 to +180°C.

TURMOSYNTHGREASE ALN 4601 is a combination of a complex soap thickener and synthetic oil. Special additives ensure high thermal and oxidation stability.

TURMOSYNTHGREASE ALN 4601 has excellent corrosion and wear properties.

TURMOSYNTHGREASE ALN 4601 fulfils the USDA-H1 regulations and meets the requirements according to § 5 of LMBG.

TECHNICAL DATA

TURMOSYNTHGREASE ALN 4601

Base oil	Synthetic oil
Worked penetraton NLGI	310 - 340
Temperature range °C short time	-30 to +180 to +200°C
Water resistance DIN 51807/T1	0 - 90
Thickener	inert organic thickener

APPLICATIONS

TURMOSYNTHGREASE ALN 4601 is especially suitable for the lubrication of roller and plain bearings at low and medium speed up to a speed factor of 220.000 (n x dm)

ORIGINAL PACKING

6 x 1 kg cans, 25 kg hobbocks