


Automatic lubrication of electric motors, pumps and fans

Why automatic lubrication?



Automatic lubrication...

...reduces your costs

- saves time
- fewer machine breakdowns due to decreased wear
- lower lubricant consumption
- increased service life of bearings

...protects the environment

- needs-based lubricant dosage
- low risk of impurities and contamination

...improves work safety

- ...enables monitoring and provides an overview

Challenges



Contamination



Costs



Safety

Rolling bearings used in electric motors, pumps or fans are at risk of various modes of failure if an incorrect maintenance strategy is implemented.

Direct contact to contamination leads to high exposure on important machine parts.

Besides, if access to lubrication points is burdensome or even dangerous, the risk of a costly machine breakdown increases.

Scopes of application

- electric motors
- pumps
- fans



Solutions



Specifications	G LUBE	SOLO LUBE	LUB 5	LUB-S	LUBRICUS
Lubrication points	Single	Single	Single	Multiple	Multiple
Ambient temperature	-20 °C to +55 °C	-20 °C to +60 °C	-20 °C to +60 °C	-15 °C to +60 °C	-15 °C to +70 °C
Working voltage	Battery	Battery/24V	Battery	Battery/24V	Battery/24V
Max. operating pressure	5 bar (73 psi)	7.5 bar (109 psi)	10 bar (145 psi)	35/50 bar (508/725 psi)	70 bar (1015 psi)
Max. tube length*	Grease: 0.5 m Oil: 3 m	Grease: 1.5 m Oil: 5 m	Grease: 2 m Oil: 5 m	Grease: 4 m Oil: 7 m	Grease: 6 m Oil: 10 m
Max. run-time	12 months	12 months	24 months	24 months	36 months
Lubricating intervals	1/3/6/9/12	1-12 (steppless)	1/3/6/12/24	1-24 (steppless)	1-36 (steppless)
Filling	By yourself or on customer request	By yourself or on customer request	By yourself or on customer request	On customer request	On customer request
Reusable drive	X	✓	✓	✓	✓
Self-refilling	X	X	✓	X	X
Time / pulse control	Time control	Time control	Time control	Time & pulse control	Time & pulse control

* depends on lubricant and application



Contamination

- automatic lubrication lowers the risk of contamination
- lower machine wear even in rough environmental conditions



Costs

- lower energy costs
- time saving
- sustainable by multiple refills
- increasing production efficiency



Safety

- indirect installation possible
- central controlling and monitoring in a user-friendly environment

